



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL26S-M0050	0.5	500	+50/-0
MIL26S-M0100	1	1000	+50/-0
MIL26S-M0150	1.5	1500	+50/-0
MIL26S-M0200	2	2000	+50/-0
MIL26S-M0300	3	3000	+50/-0
MIL26S-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG*13P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=8.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 26P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ø5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ø10.0*35MM
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1	OPEN	P1	OPEN
1 ○ BLACK		15 ○ PURPLE	
2 ○ BLACK/WHITE		16 ○ PURPLE/WHITE	
3 ○ BROWN		17 ○ GRAY	
4 ○ BROWN/WHITE		18 ○ GRAY/BLACK	
5 ○ RED		19 ○ WHITE	
6 ○ RED/WHITE		20 ○ ORANGE/BLACK	
7 ○ ORANGE		21 ○ PINK	
8 ○ ORANGE/WHITE		22 ○ RED/BLACK	
9 ○ YELLOW		23 ○ LIGHT GREEN	
10 ○ YELLOW/BLACK		24 ○ GREEN/BLACK	
11 ○ GYEEN		25 ○ PINK/BLACK	
12 ○ GREEN/WHITE		26 ○ PINK/RED	
13 ○ BLUE			
14 ○ BLUE/WHITE			

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		26P IDC TO OPEN		
PART NO.		MIL26S-MXXXX		