



CHART:

26P IDC
WITH SR

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL26S-X3-F0010	0.1	100	+15/-0
MIL26S-X3-F0020	0.2	200	+15/-0
MIL26S-X3-F0030	0.3	300	+15/-0
MIL26S-X3-F0050	0.5	500	+50/-0
MIL26S-X3-F0075	0.75	750	+50/-0
MIL26S-X3-F0100	1	1000	+75/-0
MIL26S-X3-F0150	1.5	1500	+75/-0
MIL26S-X3-F0200	2	2000	+75/-0
MIL26S-X3-F0300	3	3000	+75/-0

PIN OUT :

P1 OPEN

1 RD
 2 _____
 • _____
 • _____
 • _____
 26 _____

Note:

1. CABLE : UL 2651 28AWG*(7/0.127mm)*26C , P=1.27MM,GRAY PVC FLAT CABLE .
2. P1 CONN : 2.54MM PITCH 13*2=26 PIN IDC SOCKET WITH THREE PARTS.
3. THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE	⊕	REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	07/29/05	TITLE	
		26P IDC TO OPEN	
PART NO.		MIL26S-X3-FXXXX	