



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL26SS-M0050	0.5	500	+50/-0
MIL26SS-M0100	1	1000	+50/-0
MIL26SS-M0150	1.5	1500	+50/-0
MIL26SS-M0200	2	2000	+50/-0
MIL26SS-M0300	3	3000	+50/-0
MIL26SS-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG\*13P(ID=0.85)+AEB+PVC JACKET-BEIGE(BG-02) OD=8.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 26P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK Ø5.0\*12MM  
TUBE2:HEAT SHRINKING TUBE BLACK Ø10.0\*35MM
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1	P2	P1	P2
1	1	17	17
2	2	18	18
3	3	19	19
4	4	20	20
5	5	21	21
6	6	22	22
7	7	23	23
8	8	24	24
9	9	25	25
10	10	26	26
11	11		
12	12		
13	13		
14	14		
15	15		
16	16		

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		26P IDC TO 26P IDC TYPE		
PART NO.		MIL26SS-MXXXX		