



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL26SS-M0050	0.5	500	+50/-0
MIL26SS-M0100	1	1000	+75/-0
MIL26SS-M0150	1.5	1500	+75/-0
MIL26SS-M0200	2	2000	+75/-0
MIL26SS-M0300	3	3000	+75/-0
MIL26SS-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG*13P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG02) OD=8.5±0.15mm
- CABLE2: UL1007,16AWG(26/0.254mm),OD:2.4±0.1mm,COLOR:GN
- 26P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ϕ 5.0*12mm
TUBE2:HEAT SHRINKING TUBE BLACK ϕ 10.0*35mm
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1	P2	P1	P2
1	17	GRAY	17
2	18	GRAY/BLACK	18
3	19	WHITE	19
4	20	ORANGE/BLACK	20
5	21	PINK	21
6	22	RED/BLACK	22
7	23	LIGHT GREEN	23
8	24	GREEN/BLACK	24
9	25	PINK/BLACK	25
10	26	PINK/RED	26
11	11	GYEEN	11
12	12	GREEN/WHITE	12
13	13	BLUE	13
14	14	BLUE/WHITE	14
15	15	PURPLE	15
16	16	PURPLE/WHITE	16

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		B
SHEET	1/1	DWG NO.	
DATE	09/27/13	TITLE	
		26P IDC TO 26P IDC TYPE	
PART NO.		MIL26SS-MXXXX	