



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL34S-M0050	0.5	500	+50/-0
MIL34S-M0100	1	1000	+50/-0
MIL34S-M0150	1.5	1500	+50/-0
MIL34S-M0200	2	2000	+50/-0
MIL34S-M0300	3	3000	+50/-0
MIL34S-M0500	5	5000	+150/-0

REMARK

- CABLE:UL2464 28AWG*17P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=9.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 34P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ø 5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ø 11.0*45MM
- EACH CABLE IN A ZIP PE-BAG

PIN OUT		OPEN	
P1 1	BLACK	P1 23	LIGHT GREEN
2	BLACK/WHITE	24	GREEN/BLACK
3	BROWN	25	PINK/BLACK
4	BROWN/WHITE	26	PINK/RED
5	RED	27	PINK/BLUE
6	RED/WHITE	28	PINK/GREEN
7	ORANGE	29	LIGHT BLUE
8	ORANGE/WHITE	30	LIGHT YELLOW
9	YELLOW	31	LIGHT BLUE/BLACK
10	YELLOW/WHITE	32	LIGHT BLUE/RED
11	GYEEN	33	LIGHT BLUE/BLUE
12	GREEN/WHITE	34	LIGHT BLUE/GREEN
13	BLUE		
14	BLUE/WHITE		
15	PURPLE		
16	PURPLE/WHITE		
17	GRAY		
18	GRAY/WHITE		
19	WHITE		
20	ORANGE/BLACK		
21	PINK		
22	RED/BLACK		

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		34P IDC TO OPEN		
PART NO.		MIL34S-MXXXX		