



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL34S-X3-F0010	0.1	100	+15/-0
MIL34S-X3-F0020	0.2	200	+15/-0
MIL34S-X3-F0030	0.3	300	+15/-0
MIL34S-X3-F0050	0.5	500	+50/-0
MIL34S-X3-F0075	0.75	750	+50/-0
MIL34S-X3-F0100	1	1000	+75/-0
MIL34S-X3-F0150	1.5	1500	+75/-0
MIL34S-X3-F0200	2	2000	+75/-0
MIL34S-X3-F0300	3	3000	+75/-0

PIN OUT :

P1 OPEN

1 RD _____

2 _____

• _____

• _____

• _____

34 _____

Note:

1. CABLE : UL 2651 28AWG*(7/0.127mm)*34C , P=1.27MM,GRAY PVC FLAT CABLE .
2. P1 CONN : 2.54MM PITCH 17*2=34 PIN IDC SOCKET WITH THREE PARTS.
3. THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE	⊕	REV
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	07/29/05		
TITLE			
34P IDC TO OPEN			
PART NO.			
MIL34S-X3-FXXXX			