



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL34SS-M0050	0.5	500	+50/-0
MIL34SS-M0100	1	1000	+50/-0
MIL34SS-M0150	1.5	1500	+50/-0
MIL34SS-M0200	2	2000	+50/-0
MIL34SS-M0300	3	3000	+50/-0
MIL34SS-M0500	5	5000	+150/-0

PIN OUT

P1	1	BLACK	P2	1	BLUE	P1	25	PINK/BLACK	P2	25
2	BLACK/WHITE	2	13	BLUE/WHITE	13	26	PINK/RED	26		
3	BROWN	3	14	PURPLE	14	27	PINK/BLUE	27		
4	BROWN/WHITE	4	15	PURPLE/WHITE	15	28	PINK/GREEN	28		
5	RED	5	16	GRAY	16	29	LIGHT BLUE	29		
6	RED/WHITE	6	17	GRAY/WHITE	17	30	LIGHT YELLOW	30		
7	ORANGE	7	18	WHITE	18	31	LIGHT BLUE/BLACK	31		
8	ORANGE/WHITE	8	19	ORANGE/BLACK	19	32	LIGHT BLUE/RED	32		
9	YELLOW	9	20	PINK	20	33	LIGHT BLUE/BLUE	33		
10	YELLOW/WHITE	10	21	RED/BLACK	21	34	LIGHT BLUE/GREEN	34		
11	GYEEN	11	22	LIGHT GREEN	22					
12	GREEN/WHITE	12	23	GREEN/BLACK	23					
			24		24					

REMARK

- CABLE:UL2464 28AWG*17P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=9.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 34P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ∅5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ∅11.0*45MM
- EACH CABLE IN A ZIP PE-BAG

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE				
34P IDC TO 34P IDC TYPE				
PART NO.				
MIL34SS-MXXXX				