



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL34SS-M0050	0.5	500	+50/-0
MIL34SS-M0100	1	1000	+50/-0
MIL34SS-M0150	1.5	1500	+50/-0
MIL34SS-M0200	2	2000	+50/-0
MIL34SS-M0300	3	3000	+50/-0
MIL34SS-M0500	5	5000	+150/-0

PIN OUT			
P1		P2	
1	BLACK	1	BLUE
2	BLACK/WHITE	2	BLUE/WHITE
3	BROWN	3	PURPLE
4	BROWN/WHITE	4	PURPLE/WHITE
5	RED	5	GRAY
6	RED/WHITE	6	GRAY/WHITE
7	ORANGE	7	WHITE
8	ORANGE/WHITE	8	ORANGE/BLACK
9	YELLOW	9	PINK
10	YELLOW/WHITE	10	RED/BLACK
11	GYEEN	11	LIGHT GREEN
12	GREEN/WHITE	12	GREEN/BLACK
13		13	BLUE
14		14	BLUE/WHITE
15		15	PURPLE
16		16	PURPLE/WHITE
17		17	GRAY
18		18	GRAY/WHITE
19		19	WHITE
20		20	ORANGE/BLACK
21		21	PINK
22		22	RED/BLACK
23		23	LIGHT GREEN
24		24	GREEN/BLACK
25		25	PINK/BLACK
26		26	PINK/RED
27		27	PINK/BLUE
28		28	PINK/GREEN
29		29	LIGHT BLUE
30		30	LIGHT YELLOW
31		31	LIGHT BLUE/BLACK
32		32	LIGHT BLUE/RED
33		33	LIGHT BLUE/BLUE
34		34	LIGHT BLUE/GREEN

REMARK

- CABLE:UL2464 28AWG*17P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=9.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 34P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ∅5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ∅11.0*45MM
- EACH CABLE IN A ZIP PE-BAG

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE 34P IDC TO 34P IDC TYPE				
PART NO. MIL34SS-MXXXX				