


CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL34SS-XX2-F0010	0.1	100	+15/-0
MIL34SS-XX2-F0020	0.2	200	+15/-0
MIL34SS-XX2-F0030	0.3	300	+15/-0
MIL34SS-XX2-F0050	0.5	500	+50/-0
MIL34SS-XX2-F0075	0.75	750	+50/-0
MIL34SS-XX2-F0100	1	1000	+75/-0
MIL34SS-XX2-F0150	1.5	1500	+75/-0
MIL34SS-XX2-F0200	2	2000	+75/-0
MIL34SS-XX2-F0300	3	3000	+75/-0

PIN OUT :



Note:

1. CABLE : UL 2651 28AWG\*(7/0.127mm)\*34C , P=1.27MM,GRAY PVC FLAT CABLE .
2. P1&P2 CONN : 2.54MM PITCH 17\*2=34 PIN IDC SOCKET WITH THREE PARTS.
3. THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE 34P IDC TO 34P IDC TYPE				
PART NO. MIL34SS-XX2-FXXXX				