



PIN OUT

P1		OPEN
1	BLACK	
2	BLACK/WHITE	
3	BROWN	
4	BROWN/WHITE	
5	RED	
6	RED/WHITE	
7	ORANGE	
8	ORANGE/WHITE	
9	YELLOW	
10	YELLOW/BLACK	
11	GYEEN	
12	GREEN/WHITE	
13	BLUE	
14	BLUE/WHITE	
15	PURPLE	
16	PURPLE/WHITE	
17	GRAY	
18	GRAY/BLACK	
19	WHITE	
20	ORANGE/BLACK	

P1		OPEN
21	PINK	
22	RED/BLACK	
23	LIGHT GREEN	
24	GREEN/BLACK	
25	PINK/BLACK	
26	PINK/RED	
27	PINK/BLUE	
28	PINK/GREEN	
29	LIGHT BLUE	
30	LIGHT YELLOW	
31	LIGHT BLUE/BLACK	
32	LIGHT BLUE/RED	
33	LIGHT BLUE/BLUE	
34	LIGHT BLUE/GREEN	
35	GREY/RED	
36	GREY/GREEN	
37	BLUE/BLACK	
38	PURPLE/BLACK	
39	LIGHT GREEN/BLACK	
40	LIGHT GREEN/RED	

CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL40S-M0050	0.5	500	+50/-0
MIL40S-M0100	1	1000	+50/-0
MIL40S-M0150	1.5	1500	+50/-0
MIL40S-M0200	2	2000	+50/-0
MIL40S-M0300	3	3000	+50/-0
MIL40S-M0500	5	5000	+150/-0

REMARK

- CABLE:UL2464 28AWG\*20P(ID=0.85)+AEB+PVC  
JACKET:BEIGE(BG-02) OD=9.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 40P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL.
- TUBE1:HEAT SHRINKING TUBE BLACK∅ 5.0\*12MM  
TUBE2:HEAT SHRINKING TUBE BLACK∅ 11.0\*45MM
- EACH CABLE IN A ZIP PE-BAG

NET MECHANISM Corp  
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
PART NO.		MIL40S-MXXXX		