



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL40SS-M0050	0.5	500	+50/-0
MIL40SS-M0100	1	1000	+75/-0
MIL40SS-M0150	1.5	1500	+75/-0
MIL40SS-M0200	2	2000	+75/-0
MIL40SS-M0300	3	3000	+75/-0
MIL40SS-M0500	5	5000	+150/-0

REMARK

1. CABLE:UL2464 28AWG*20P(ID=0.85)+AEB+PVC
JACKET:BEIGE(BG-02) OD=9.5±0.15mm
2. CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
3. 40P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
4. TERMINAL: Y TYPE TERMINAL.
5. TUBE1:HEAT SHRINKING TUBE BLACK∅ 5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK∅ 11.0*45MM
6. EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1		P2
1	BLACK	1
2	BLACK/WHITE	2
3	BROWN	3
4	BROWN/WHITE	4
5	RED	5
6	RED/WHITE	6
7	ORANGE	7
8	ORANGE/WHITE	8
9	YELLOW	9
10	YELLOW/BLACK	10
11	GYEEN	11
12	GREEN/WHITE	12
13	BLUE	13
14	BLUE/WHITE	14
15	PURPLE	15
16	PURPLE/WHITE	16
17	GRAY	17
18	GRAY/BLACK	18
19	WHITE	19
20	ORANGE/BLACK	20

P1		P2
21	PINK	21
22	RED/BLACK	22
23	LIGHT GREEN	23
24	GREEN/BLACK	24
25	PINK/BLACK	25
26	PINK/RED	26
27	PINK/BLUE	27
28	PINK/GREEN	28
29	LIGHT BLUE	29
30	LIGHT YELLOW	30
31	LIGHT BLUE/BLACK	31
32	LIGHT BLUE/RED	32
33	LIGHT BLUE/BLUE	33
34	LIGHT BLUE/GREEN	34
35	GREY/RED	35
36	GREY/GREEN	36
37	BLUE/BLACK	37
38	PURPLE/BLACK	38
39	LIGHT GREEN/BLACK	39
40	LIGHT GREEN/RED	40

Y TERMINAL — DRAIN+BRAID — Y TERMINAL

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/01/13			
TITLE		40P IDC TO 40P IDC TYPE		
PART NO.		MIL40SS-MXXXX		