



REMARK

1. CABLE:UL2464 28AWG*25P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02)
OD=10.5±0.15mm.
2. CABLE2: UL1007,16AWG(26/0.254),OD:2.4±0.1mm,COLOR:GN
3. 50P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
4. TERMINAL: Y TYPE TERMINAL.
5. TUBE1:HEAT SHRINKING TUBE BLACK ϕ 5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ϕ 12.0*45MM
6. EACH CABLE IN A ZIP PE-BAG

PIN OUT			
P1	1	P2	1
	2		2
	3		3
	4		4
	5		5
	6		6
	7		7
	8		8
	9		9
	10		10
	11		11
	12		12
	13		13
	14		14
	15		15
	16		16
	17		17
	18		18
	19		19
	20		20
	21		21
	22		22
	23		23
	24		24
	25		25
	26		26
	27		27
	28		28
	29		29
	30		30
	31		31
	32		32
	33		33
	34		34
	35		35
	36		36
	37		37
	38		38
	39		39
	40		40
	41		41
	42		42
	43		43
	44		44
	45		45
	46		46
	47		47
	48		48
	49		49
	50		50

CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL50SS-M0050	0.5	500	+50/-0
MIL50SS-M0100	1	1000	+75/-0
MIL50SS-M0150	1.5	1500	+75/-0
MIL50SS-M0200	2	2000	+75/-0
MIL50SS-M0300	3	3000	+75/-0
MIL50SS-M0500	5	5000	+150/-0

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		B
SHEET	1/1	DWG NO.	
DATE	11/18/13	TITLE	
		50P IDC TO 50P IDC TYPE	
PART NO.		MIL50SS-MXXXX	