



REMARK

1. CABLE:UL2464 28AWG*25P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02)
OD=10.5? 0.15MM
2. CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
3. 50P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
4. TERMINAL: Y TYPE TERMINAL.
5. TUBE1:HEAT SHRINKING TUBE BLACK ϕ 5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ϕ 12.0*45MM
6. EACH CABLE IN A ZIP PE-BAG

PIN OUT					
P1	1	BLACK	P2	1	LIGHT BLUE
2	BLACK/WHITE	2	30	LIGHT YELLOW	
3	BROWN	3	31	LIGHT BLUE/BLACK	
4	BROWN/WHITE	4	32	LIGHT BLUE/RED	
5	RED	5	33	LIGHT BLUE/BLUE	
6	RED/WHITE	6	34	LIGHT BLUE/GREEN	
7	ORANGE	7	35	GREY/RED	
8	ORANGE/WHITE	8	36	GREY/GREEN	
9	YELLOW	9	37	BLUE/BLACK	
10	YELLOW/BLACK	10	38	PURPLE/BLACK	
11	GYEEN	11	39	LIGHT GREEN/BLACK	
12	GREEN/WHITE	12	40	LIGHT GREEN/RED	
13	BLUE	13	41	LIGHT GREEN/BLUE	
14	BLUE/WHITE	14	42	LIGHT GREEN/GREEN	
15	PURPLE	15	43	LIGHT YELLOW/BLACK	
16	PURPLE/WHITE	16	44	LIGHT YELLOW/RED	
17	GRAY	17	45	LIGHT YELLOW/BLUE	
18	GRAY/BLACK	18	46	LIGHT YELLOW/GREEN	
19	WHITE	19	47	WHITE/BLACK	
20	ORANGE/BLACK	20	48	WHITE/RED	
21	PINK	21	49	WHITE/BLUE	
22	RED/BLACK	22	50	WHITE/GREEN	
23	LIGHT GREEN	23			
24	GREEN/BLACK	24			
25	PINK/BLACK	25			
26	PINK/RED	26			
27	PINK/BLUE	27			
28	PINK/GREEN	28			

CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL50SS-M0050	0.5	500	+50/-0
MIL50SS-M0100	1	1000	+50/-0
MIL50SS-M0150	1.5	1500	+50/-0
MIL50SS-M0200	2	2000	+50/-0
MIL50SS-M0300	3	3000	+50/-0
MIL50SS-M0500	5	5000	+150/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE 50P IDC TO 50P IDC TYPE				
PART NO. MIL50SS-MXXXX				