



NOTE:

1. CABLE: 28AWG X 25C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (BG-03) PVC JACKET OD7.0±0.15mm.
2. CONNECTOR: P1: D-SUB 25PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: CENTRONICS 36PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS.
- ③ THUMB SCREW TO BE MOLDED.
4. AL FOIL 360° CONTACTED WITH SHELL BOTH END
5. ALL HOOD: MOLDED BEIGE(BG-03) PVC.
6. TESTING:100% ELECTRICAL TESTING.

PIN OUT					
P1	P2	P1	P2	P1	P2
1	1	10	10	19	19
2	2	11	11	20	21
3	3	12	12	21	23
4	4	13	13	22	25
5	5	14	14	23	27
6	6	15	32	24	29
7	7	16	31	25	30
8	8	17	36		
9	9	18	33		

SHELL—— SHELL(DRAIN WIRE)

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
PR1-25M36M-03	03	914	+50/-0
PR1-25M36M-06	06	1829	+75/-0
PR1-25M36M-10	10	3048	+75/-0
PR1-25M36M-15	15	4572	+75/-0

<b>NET MECHANISM Corp</b> www.cabling-ol.net			
SCALE	NONE		REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/13/04		
TITLE			
DB25M TO CN36M			
PART NO.			
PR1-25M36M-XX			