



### WIRE LIST

P1		P2
1	CENTER	1
2	SHELL	2

### REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1 AND P2:RCA JACK,NICKEL PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2Kg.
- 4.ELECTRONIC CHARACTERISTICS: CONTACT RESISTANCE:20M  $\Omega$   
INSULATION RESISTANC: 2M  $\Omega$ WITHSTAND VOLTAGE AC:200V DC:250V,  
CURRENT RATING AC: 100V/0.5A DC:150V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LIFE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE RCA/F TO RCA/F ADAPTER				
PART NO. RCAF-RCAF				