



| P/N | X(M) | L(MM) | TOLERANCE(MM) |
|------------|------|-------|---------------|
| RJ11-F0300 | 3 | 3000 | +75/-0 |
| RJ11-F0500 | 5 | 5000 | +150/-0 |
| RJ11-F1000 | 10 | 10000 | +150/-0 |
| RJ11-F2000 | 20 | 20000 | +300/-0 |

PIN OUT

| P1 | P2 |
|---------|----|
| 2 ————— | 2 |
| 3 ————— | 3 |
| 4 ————— | 4 |
| 5 ————— | 5 |

NOTE:

1. CABLE: CONDUCTOR:TINSEL 32AWG(4H),JACKET:90P PVC
OD:0.95*4.1MM,BLACK(ATOMIZER).
2. CONNECTOR: P1&P2: RJ11 6P4C MOUDLAR GOLD 2-3U".
3. CABLE ASS'Y MUST PASS CONTINUITY TEST.

| | | | | |
|--|----------|---------|-----|---|
| NET MECHANISM Corp www.cabling-ol.net | | | | |
| SCALE | NONE | | REV | A |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 06/17/05 | | | |
| TITLE RJ11 6P4C TO RJ11 6P4C FLAT CABLE | | | | |
| PART NO. RJ11-FXXXX | | | | |