



P/N	X(M)	L(MM)	T(MM)
RJ11-S0300	3	3000	+75/-0
RJ11-S0500	5	5000	+150/-0
RJ11-S1000	10	10000	+150/-0
RJ11-S2000	20	20000	+300/-0
RJ11-S3000	30	30000	+300/-0
RJ11-S5000	50	50000	+500/-0

PIN OUT

P1	P2	
2	2	GREEN
5	5	WHITE
3	3	RED
4	4	BLACK
SHELL	SHELL	(DRAIN)

NOTES:

1. CABLE: 26AWG*2PAIRS, AL-FOIL SHIELDED WITH DRAIN WIRE, UL20251, WHITE JACKET PVC, OD: $\phi 5.0 \pm 0.15$ MM.
2. CONNECTOR: P1 & P2: RJ11 6P4C PLUG, GOLD FLASH CONTACTS, WITH SHELL.
3. CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/27/09			
TITLE				
6P4C PLUG/6P4C PLUG				
PART NO.				
RJ11-SXXXX				