



NOTES:

1. CABLE: SERIAL ATA CABLE:{26AWG(1/0.404)*2C+AL.MY+ DRAIN WIRE[28AWG(1/0.32)*2C]}*2F,OD:2.3*8.30mm RED PVC JACKET.(P/N:B-SATA-03).
2. CONNECTOR: P1&P2 :SERIAL ATA 7PIN PLUG,CRIMPING TYPE, GOLD PLATED CONTACTS.(P/N:C-SATA7M-03).
3. HOOD: MOLDED BLACK PVC.
- 4.ELECTRICAL PROPERTIES:
 - (1).IT SHALL HAVE NOT ANY OPEN/SHORT,MISWIRING AND INTERMITTENT.
 - (2).THE CABLE SHALL BE 100% ELECTRICAL TEST.
 - (3).INSULATION RESISTANCE:100M OHM MIN.
 - (4).CONDUCTANCE RESISTANCE:2 OHM MAX.
 - (5).HI-POT TEST:DC 300 MIN.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	D
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/13			
TITLE				
SATA7P TO SATA 7P 180				
PART NO.				
SATA-STST-XX				