



| L     | TOLERANCE(MM) |
|-------|---------------|
| L<=1M | +50/-0        |
| L>1M  | +100/-0       |

Specification:

- |                   |            |               |                |
|-------------------|------------|---------------|----------------|
| 1. Connector A    | SC/PC M/M  | P/N: 880-SC-M | BOOT:BLACK&RED |
| 2. Connector B    | SC/PC M/M  | P/N: 880-SC-M | BOOT:BLACK&RED |
| 3. Cable Type     | Duplex M/M | 50/125uM      | ø2.8*5.7mm     |
| 4. Length         | XX         | (UNIT:METER)  |                |
| 5. Jacket Color   | Orange     |               |                |
| 6. Insertion Loss | <0.10      | dB            |                |

| NET MECHANISM Corp<br>www.cabling-ol.net    |          |         |     |   |
|---|----------|---------|-----|---|
| SCALE                                       | NONE     |         | REV | A |
| UNIT  | MM       |         |     |   |
| SHEET                                       | 1/1      | DWG NO. |     |   |
| DATE  | 06/22/05 |         |     |   |
| TITLE                                       |          |         |     |   |
| SC TO SC Multimode 50/125uM FIBER PATCHCORD |          |         |     |   |
| PART NO.                                    |          |         |     |   |
| SC-SC-50MXX                                 |          |         |     |   |