



| L(mm) | TOLERANCE(mm) |
|--------------|---------------|
| 100~499 | +25/-0 |
| 500~999 | +50/-0 |
| 1000~4999 | +75/-0 |
| 5000~14999 | +150/-0 |
| 15000~49999 | +300/-0 |
| 50000~100000 | +500/-0 |

Specification:

- | | | |
|-------------------|-----------------------------------|-------------------|
| 1. Connector A | SC/PC M/M | BOOT:BLACK OR RED |
| 2. Connector B | SC/PC M/M | BOOT:BLACK OR RED |
| 3. Cable Type | Simplex M/M 50/125uM ϕ 2.8mm | |
| 4. Length | METER | |
| 5. Jacket Color | ORANGE | |
| 6. Insertion Loss | <0.10 dB | |

| NET MECHANISM Corp www.cabling-ol.net | | | | |
|--|----------|---------|-----|---|
| SCALE | NONE | | REV | A |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 06/22/10 | | | |
| TITLE | | | | |
| SC-SC Simplex 50/125 Fiber Patchcords. | | | | |
| PART NO. | | | | |
| SC-SC-50MXX-SP | | | | |