



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
SFCN40-MIL40-C005	0.5	500	+50/-0
SFCN40-MIL40-C010	1	1000	+75/-0
SFCN40-MIL40-C015	1.5	1500	+75/-0
SFCN40-MIL40-C020	2	2000	+75/-0
SFCN40-MIL40-C030	3	3000	+75/-0
SFCN40-MIL40-C050	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG*20P(ID=0.85)+AEB+PVC
JACKET:BEIGE(BG-02) OD=9.5±0.15MM.
CABLE2:UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN.
- CONN1: FUJITSU P/N:FCN-361J040-AU AND FCN-360C040-B.
CONN2: 40P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE.
- TERMINAL: Y TYPE TERMINAL.
- TUBE1:HEAT SHRINKING TUBE BLACK OD:5.0*12MM.
TUBE2:HEAT SHRINKING TUBE BLACK OD:11*40MM,OD:11*45MM.
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1		P2	P1	P2
A1	— 0 — BLACK	1	A11	— 0 — PINK
B1	— 0 — BLACK/WHITE	2	B11	— 0 — RED/BLACK
A2	— 0 — BROWN	3	A12	— 0 — LIGHT GREEN
B2	— 0 — BROWN/WHITE	4	B12	— 0 — GREEN/BLACK
A3	— 0 — RED	5	A13	— 0 — PINK/BLACK
B3	— 0 — RED/WHITE	6	B13	— 0 — PINK/RED
A4	— 0 — ORANGE	7	A14	— 0 — PINK/BLUE
B4	— 0 — ORANGE/WHITE	8	B14	— 0 — PINK/GREEN
A5	— 0 — YELLOW	9	A15	— 0 — LIGHT BLUE
B5	— 0 — YELLOW/BLACK	10	B15	— 0 — LIGHT YELLOW
A6	— 0 — GYEEN	11	A16	— 0 — LIGHT BLUE/BLACK
B6	— 0 — GREEN/WHITE	12	B16	— 0 — LIGHT BLUE/RED
A7	— 0 — BLUE	13	A17	— 0 — LIGHT BLUE/BLUE
B7	— 0 — BLUE/WHITE	14	B17	— 0 — LIGHT BLUE/GREEN
A8	— 0 — PURPLE	15	A18	— 0 — GREY/RED
B8	— 0 — PURPLE/WHITE	16	B18	— 0 — GREY/GREEN
A9	— 0 — GRAY	17	A19	— 0 — BLUE/BLACK
B9	— 0 — GRAY/BLACK	18	B19	— 0 — PURPLE/BLACK
A10	— 0 — WHITE	19	A20	— 0 — LIGHT GREEN/BLACK
B10	— 0 — ORANGE/BLACK	20	B20	— 0 — LIGHT GREEN/RED
				— 0 — BRAID+DRAIN —

NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	08/15/05	TITLE	
		FCN 40F TO IDC 40F	
PART NO.		SFCN40-MIL40-CXXX	