



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
SFCN40-MIL40-C005	0.5	500	+50/-0
SFCN40-MIL40-C010	1	1000	+75/-0
SFCN40-MIL40-C015	1.5	1500	+75/-0
SFCN40-MIL40-C020	2	2000	+75/-0
SFCN40-MIL40-C030	3	3000	+75/-0
SFCN40-MIL40-C050	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG\*20P(ID=0.85)+AEB+PVC  
JACKET:BEIGE(BG-02) OD=9.5±0.15MM.  
CABLE2:UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN.
- CONN1: FUJITSU P/N:FCN-361J040-AU AND FCN-360C040-B.  
CONN2: 40P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE.
- TERMINAL: Y TYPE TERMINAL.
- TUBE1:HEAT SHRINKING TUBE BLACK OD:5.0\*12MM.  
TUBE2:HEAT SHRINKING TUBE BLACK OD:11\*40MM,OD:11\*45MM.
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1	P2	P1	P2
A1	1	A11	21
B1	2	B11	22
A2	3	A12	23
B2	4	B12	24
A3	5	A13	25
B3	6	B13	26
A4	7	A14	27
B4	8	B14	28
A5	9	A15	29
B5	10	B15	30
A6	11	A16	31
B6	12	B16	32
A7	13	A17	33
B7	14	B17	34
A8	15	A18	35
B8	16	B18	36
A9	17	A19	37
B9	18	B19	38
A10	19	A20	39
B10	20	B20	40
		TERM	TERM

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	08/15/05	TITLE	
		FCN 40F TO IDC 40F	
PART NO.		SFCN40-MIL40-CXXX	