


WIRE LIST

P2	P1	P3
1 — CENTER	1	
	2 — CENTER	1
2 — SHELL	3 — SHELL	2

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:3.5mm STEREO PLUG,GOLD PLATED SHELL AND P2 P3:RCA JACK.GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:20M Ω
INSULATION RESISTANC: 2MΩWITHSTAND VOLTAGE AC:100V DC:150V
CURRENT RATING AC: 100V/0.5A DC:150V/1A
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/08/06			
TITLE ø3.5mm STEREO PLUG TO 2RCA/F				
PART NO. SM-2RCAF				