



P/N	X(M)	L(MM)	TOLERANCE(MM)
SMABNC-0050	0.5	500	+25/-0
SMABNC-0100	1	1000	+50/-0
SMABNC-0200	2	2000	+50/-0
SMABNC-0300	3	3000	+75/-0

PIN OUT :



NOTE:

- 1.CABLE:RG174/U 26AWGx1C(7/0.16 TINNED COPPER)+PE INSULATION+BRAID(16\*4/0.12),PVC JACKET,COLOR: BLACK(BK), $\phi 3.0 \pm 0.15$ mm.
- 2.CONN.:P1: SMA CONN, GOLD FLASH CONTACTS,50 OHM.(RG174U)
- 3.CONN.:P2: BNC MALE, GOLD FLASH CONTACTS, 50 OHM.(RG174U)
- 4.HOOD: 45P PVC BLACK(BK).
- 5.H.S.T: $\phi 3.5 \times 15$ mm BLACK
- 6.TESTING:100% ELECTRICAL TEST.
- 7.PACKING:EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE SMA TO BNC/M				
PART NO. SMABNC-XXXX				