


NOTES:

1. CABLE: UL2725 USB 1.1 CABLE, (28AWG*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), PVC JACKET,COLOR:(BG-02). OD:4.5±0.10mm.
2. CONNECTOR: P1 & P2: USB A TYPE MALE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
3. HOOD: MOLDED (BG-02) PVC.
4. TESTING:100% ELECTRICAL TESTING.

PIN OUT

	P1		P2	
24AWG	1	—————	1	RED
28AWG	2	———○———	2	WHITE
28AWG	3	———○———	3	GREEN
24AWG	4	—————	4	BLACK
	SHELL	—————	SHELL	(BRAID)



A01

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB-AMAM-03	3	914	+50/-0
USB-AMAM-06	6	1829	+75/-0
USB-AMAM-10	10	3048	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/25/07			
TITLE		USB AM TO USB AM		
PART NO.		USB-AMAM-XX		