

NOTES:

1. CABLE: UL2725 USB 1.1 REV CABLE.(28AWG*1PAIR + 24AWG X 2C), AL-FOIL AND BRAID SHIELED(A-MALLOY) WITH A DRAIN WIRE(BARE COPPER),COLOR:BG-02. PVC JACKET, OD:4.5±0.10mm..
2. CONNECTOR: P1 & P2: USB A TYPE MALE, WHITE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
3. HOOD: MOLDED (BG-02) PVC.
4. TESTING:100% ELECTRICAL TESTING.

PIN OUT

	P1	P2	
24AWG	1	1	RED
28AWG	2	2	WHITE
28AWG	3	3	GREEN
24AWG	4	4	BLACK
SHELL			SHELL(DRAIN)




CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB-AMAM-03	3	914	+50/-0
USB-AMAM-06	6	1829	+75/-0
USB-AMAM-10	10	3048	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/20/10			
TITLE	USB AM TO USB AM			
PART NO.	USB-AMAM-XX			