



P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB2-AMAF-03	03	914	+50/-0
USB2-AMAF-06	06	1829	+75/-0
USB2-AMAF-10	10	3048	+75/-0
USB2-AMAF-15	15	4572	+75/-0



NOTES:

- CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR+ 20AWG*2C),AL-FOIL AND BRAID SHIELDED(A-MALLOY) WITH A DRAIN WIRE(BARE COPPER),PVC JACKET BLACK OD:4.8±0.15MM.
- CONNECTOR:P1:USB A TYPE MALE,WHITE PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL. P2: USB A TYPE FEMALE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL.
- HOOD: MOLDED 45P PVC BLACK(BK) PVC.
- MOLDED NO:P1:USB-AM01.P2:USB-AF01
- PACKING:EACH CABLE IN A ZIP-LOCK POLY-BAG.
- 100% ELECTRICAL TESTING.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/28/11			
TITLE	USB AM TO USB AF			
PART NO.	USB2-AMAF-XX			