


P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB2-AMAM-03	03	914	+50/-0
USB2-AMAM-06	06	1829	+75/-0
USB2-AMAM-10	10	3048	+75/-0

PIN OUT

	P1		P2	
20AWG	1	—————	1	RED
28AWG	2	⊗	2	WHITE
28AWG	3	⊙	3	GREEN
20AWG	4	—————	4	BLACK
	SHELL	—————	SHELL(BRAID)	



A01

NOTES:

1. CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR + 20AWG X 2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE(24AWG), BLACK(BK) PVC JACKET, OD:4.8±0.1mm.
2. CONNECTOR: USB A TYPE MALE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL.
3. HOOD: MOLDED 45P PVC BLACK(BK) PVC.MOLDED NO:USB-AM01.
4. PACKING:EACH CABLE IN A ZIP-LOCK POLY-BAG.
5. 100% ELECTRICAL TESTING.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/25/07			
TITLE				
USB AM TO USB AM				
PART NO.				
USB2-AMAM-XX				