



P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB2-AMMBMG-03	03	914	+50/-0
USB2-AMMBMG-06	06	1829	+75/-0
USB2-AMMBMG-10	10	3048	+75/-0
USB2-AMMBMG-15	15	4572	+75/-0

PIN OUT :

P1	P2	
1	1	RED
2	2	WHITE
3	3	GREEN
4	5	BLACK
SHELL	SHELL	(DRAIN)

> PAIR

NOTES:

1. CABLE: UL2725 USB 2.0 REV CABLE.(28AWG*1PAIR + 28AWG X 2C), AL-FOIL AND BRAID SHIELDED(A-MALLOY) WITH A DRAIN WIRE(28AWG BARE COPPER),BLACK PVC JACKET, OD:0.15±0.004”(3.8±0.1mm).
2. CONNECTOR: P1:USB A TYPE MALE, SOLDER TYPE, WHITE PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL. P2:MINI USB 2.0 REV B TYPE 5P MALE,SOLDER TYPE, PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL.
3. MOLDED 45P PVC BLACK(BK).MOLD NO:P1.USB-AM01;P2.UMBM-01
4. PACKING:EACH CABLE IN A ZIP-LOCK POLY-BAG.
5. 100% ELECTRICAL TESTING.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/20/11			
TITLE				
USB AM TO MINI USB BM				
PART NO.				
USB2-AMMBMG-XX				