



WIRE LIST:

P1		P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
SHELL	SHIELD	SHELL

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
USB2-AMPAF-01	01	300	+15/-0
USB2-AMPAF-03	03	900	+50/-0
USB2-AMPAF-06	06	1800	+75/-0

NOTE:

- CABLE:UL2725 USB 2.0 CABLE 28AWG*1P+20AWG*2C+AEB OD: Ø4.8mm BLACK PVC JACKET.
- CONN:
 P1: USB A TYPE MALE, SOLDED TYPE,WHITE PBT INSULATIPON,GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
 P2 :USB A TYPE FEMALE, SOLDED TYPE,WHITE PBT INSULATIPON,GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
- HOOD: P1:MOLDED 45P BLACK PVC,P2:MOLDED 25P BLACK PVC.
- MOLD NO.: USB-AM01,USB-AF03.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/07			
TITLE	USB A M TO USB A F			
PART NO.	USB2-AMPAF-XX			