

NOTE:

1. CABLE: UL2725 USB 2.0 CABLE, (30AWG*1PAIR + 30AWG*2C), AL-FOIL AND BRAID SHIELDED WITH A DRAIN WIRE, PVC JACKET, COLOR: WHITE (WH-05). OD: $\phi 2.55 \sim \phi 2.65$ mm.
2. CONNECTOR: P1: USB A TYPE MALE, SOLDER TYPE, SHORT TYPE, BLACK PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL. P2: USB B TYPE MALE, SOLDER TYPE, SHORT TYPE, BLACK PBT INSULATION, GOLD PLATED CONTACTS, GOLD PLATED SHELL.
3. HOOD: MOLDED 45P WHITE (WH-05) PVC.
4. TESTING: 100% ELECTRICAL TESTING.
5. MOLD NO.: USB-AM03; USB-BM03.

PIN OUT

P1 ——— P2

30AWG	1	—————	1	RED
30AWG	2	—————	2	WHITE
30AWG	3	—————	3	GREEN
30AWG	4	—————	4	BLACK
	SHELL	—————	SHELL	(BRAID+DRAIN)




CHART 1

P/N	L	T
USB2-R2WH-AMBM-M003	300	+15/-0
USB2-R2WH-AMBM-M005	500	+50/-0
USB2-R2WH-AMBM-M010	1000	+75/-0
USB2-R2WH-AMBM-M015	1500	+75/-0
USB2-R2WH-AMBM-M020	2000	+75/-0
USB2-R2WH-AMBM-M030	3000	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	09/20/06			
TITLE USB A/M TO USB B/M				
PART NO. USB2-R2WH-AMBM-MXXX				