



P/N	XX(FT)	L(MM)	TOLERANCE(MM)
VD-SVMSVMG-03	03	914	+50/-0
VD-SVMSVMG-06	06	1829	+75/-0
VD-SVMSVMG-12	12	3658	+75/-0
VD-SVMSVMG-17	17	5182	+150/-0
VD-SVMSVMG-25	25	7620	+150/-0
VD-SVMSVMG-33	33	10058	+150/-0
VD-SVMSVMG-50	50	15240	+300/-0

PIN OUT



SHELL — SHELL(BRAID)



NOTE:

- CABLE: UL20276 30AWG\*2COAX(UL1354 75ohm)+AL-FOIL SHIELDED WITH DRAIN WIRE+BRAID SHIELDED+BLACK PVC JACKET. OD:5.0±0.15mm.
- CONNECTOR: P1 & P2: MINI DIN 4PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS,GOLD PLATED SHELL.
- SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
- ALL HOOD: MOLDED BLACK PVC.MOLD NO:MD6M-01
- TESTING:100% ELECTRICAL TESTING.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/14/07			
TITLE		MD4/M TO MD4/M		
PART NO.		VD-SVMSVMG-XX		