



WIRE CONNECTION

P1	P2	COLOR	P1	P2	COLOR
1	2	WHITE	10	23	WHITE
3	1	BROWN	12	24	BLUE
2	3	DRAIN	11	22	DRAIN
4	10	WHITE	15	6	RED
6	9	RED	16	7	WHITE
5	11	DRAIN	17	15	YELLOW
7	18	WHITE	18	14	ORANGE
9	17	GREEN	19	16	PURPLE
8	19	DRAIN			
			P3		
		RED	1	13	BLUE
		WHITE	2	14	GREEN
		SPIRAL SHELL		SHELL	SHELL DRAIN

NOTE:

- CABLE-21: High speed HDMI® CABLE UL20276 (28AWG*1P+AL+D+MYLAR)*4C+28AWG*1P+28AWG*5C+AL/MY+DRAIN(BARE COPPER)+BRAID(A-M ALLOY) JACKET COLOR:BLACK OD:6.5±0.15mm.
CABLE-2: NO-UL, 26AWG*2C+SPIRAL SHIELD, BLACK PVC JACK, OD: 3.0±0.15mm.
- CONNECTOR:P1: DIN 19P MALE, SOLDER TYPE, TINNED PLATED CONTACTS,INSULATION: BLACK, NICKEL PLATED SHELL, LOCKER TYPE.
P2: DVI-D 18+1 MALE,PIN:G/F,INSULATION BLACK, NICKEL PLATED SHELL.
P3: DC3.5mm STEREO PLUG, NICKEL PLATED SHELL.
- SCREW MOLDED BLACK PVC.
- SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE DRAIN.
- P1 MOLDED 45P YELLOW(YL02) PVC,P2 AND P3 MOLDED 45P BLACK PVC.
- TESTING: 100% ELECTRICAL TEST .
- MOLD P/N: DVI-01, D14M-N01, D14M-02.DC35-01.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/03/10			
TITLE DIN 19/M TO DVI18+1M+3.5STEREO PLUG				
PART NO. DIN19M-DVIM35M-M003				