



P/N	X(M)	L(MM)	TOLERANCE(MM)
HWCB-MD81MM-05	5	5000	+150/-0
HWCB-MD81MM-07	7	7000	+150/-0
HWCB-MD81MM-10	10	10000	+150/-0
HWCB-MD81MM-15	15	15000	+300/-0
HWCB-MD81MM-20	20	20000	+300/-0
HWCB-MD81MM-30	30	30000	+300/-0
HWCB-MD81MM-45	45	45000	+300/-0

### PIN OUT

P1	P2	COLOR
1	1	RED COAX
2	2	RED SPIRAL
3	3	GREEN COAX
4	4	GREEN SPIRAL
ADD PIN	ADD PIN	BLUE COAX
5	5	BLUE SPIRAL
6	6	BLACK COAX
7	7	BLACK/WHITE SPIRAL
8	8	WHITE COAX

### NOTE:

- CABLE: UL20276 UL1354(30AWG+S)\*5COAX+PAPER JACKET PVC  
BLACK OD:7.0±0.15MM
- CONNECTOR: P1&P2: MINI DIN 8+1PIN MALE: SOLDER TYPE,  
GOLD FLASH CONTACTS, BLACK INSULATION, NICKEL PLATED. SHELL..
- ALL HOOD: MOLDED BLACK PVC.
- TESTING:100% ELECTRICAL TESTING.
- MOLD NO: MD6M-01, MD6M-N01;

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	02/12/09			
TITLE MD8+1M TO MD8+1M				
PART NO. HWCB-MD81MM-XX				