



NOTE:

1. CABLE: UL20276 UL1354(30AWG+S)*5COAX(OFC)+PAPER JACKET PVC BLACK OD:7.0±0.15MM
2. CONNECTOR: P1: MINI DIN 8+1PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS, BLACK INSULATION, NICKEL PLATED. SHELL.
P2, P3: RCA FEMALE: NICKEL PLATED CONTACTS AND SHELL, SOLDER TYPE.
P4: MD4 FEMALE: NICKEL PLATED CONTACTS AND SHELL.
3. JAPAN PLASTIC FACE PATE:3PORTS.WHYTE PAINTED.
4. JAPAN 120 TYPE WALL PLATE: MATERIAL:STAINLESS STEEL, 0.6MM.
5. SCREW:M3.5(PITCH=0.6MM),L=6MM,NICKEL PLATED.
6. P1 MOLDED 45P BLACK PVC,P2~P4 MOLDED 25P WHITE(WH05) PVC.
7. TESTING: 100% ELECTRICAL TEST.
8. PACKING: EACH CABLE IN A BOX.
9. MOLD NO.: MD6F-N01, MD6F-01, RCA-N06,RCA-06.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/02/10			
TITLE MD8+1F TO 2RCA/F+MD4F+FACE PLATE				
PART NO. SFPC-MD4F-2RCAF-120				