



- NOTE:
- CABLE: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, UL1354) + (28AWG X 4C) + (28AWG X 2PAIRS)], AL-FOIL AND BRAID(65% A-MALLOY) SHIELDED WITH DRAIN WIRE(BARE COPPER), UL2919,BLACK PVC JACKET, SLOT $\varnothing 9.0 \pm 0.15$ mm..
CABLE2:NO-UL, 26AWG*2C+SPIRAL SHIELD,BLACK PVC JACK, $0D3.0 \pm 0.15$ mm.
 - CONN.:
P1: DIN 14P MALE, NICKEL PLATED CONTACTS AND SHELL, LOCKER TYPE.
P2: HIGH DENSITY D-SUB 15PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
P3: DC3.5mm STEREO JACK, NICKEL PLATED SHELL, WITH NUT.
 - HEX NUT.
 - SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 100% CONTACT TO CONNECTOR SHELL.
P1: COPPER FOIL TAPE 360° SOLDER; P2: COPPER FOIL TAPE SOLDER TO DRAIN.
 - MOLDING BLACK 45 PVC.
 - TEST: 100% ELECTRICAL TEST.
 - MOLD NO.:D14M-N01,D14M-02.HD15F-110-01,HD15F-110-N01,RCA-03,RCA-N03.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/16/11			
TITLE DIN 14/M TO HD15/F+3.5ST/F				
PART NO. SICC-HD15F-35F-130				