



PIN OUT

P1	P2 COLOR	P1	P2 COLOR
1	WHITE	10	WHITE
3	BROWN	12	BLUE
2	DRAIN	11	DRAIN
4	WHITE	13	PURPLE
6	RED	14	RED
5	DRAIN	15	YELLOW
7	WHITE	16	ORANGE
9	GREEN	17	BLUE
8	DRAIN	18	GREEN
		19	WHITE
		SHELL	SHELL DRAIN

NOTE:

- CABLE: High speed HDMI® CABLE UL20276 (28AWG\*1P+AL+D+MYLAR)\*4C+28AWG\*1P+28AWG\*5C+AL/MY+DRAIN(BARE COPPER)+BRAID(A-M ALLOY) JACKET COLOR:BLACK OD:6.5±0.15mm.
- CONNECTOR: P1: DIN 19P MALE, SOLDER TYPE, TINNED PLATED CONTACTS, INSULATION:BLACK, NICKEL PLATED SHELL. P2:HDMI 19P FEMALE:BLACK,GOLD PLATED CONTACTS;GOLD PLATED SHELL.
- P1 SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE DRAIN.
- MODULE:BLANK SNAP INSERT MODULE,MATERIAL:PC+ABS,COLOR:WHITE.
- HOOD: P1: MOLDED BLACK PVC;P2: MOLDED 25P WHITE(WH05) PVC.
- 100% OPEN AND SHORT TESTING.
- MOLD NO: D14M-N01, D14M-02, HDMI-11, HDMI-N11.

NET MECHANISM Corp <a href="http://www.cabling-ol.net">www.cabling-ol.net</a>				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/15/11			
TITLE	DIN19M TO HDMI19F			
PART NO.	SICC-HDMIF-130			