



WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:6.35MM STEREO PLUG,GOLD PLATED SHELL AND P2:3.5MM STEREO JACK,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:10M  $\Omega$   
INSULATION RESISTANC: 20M $\Omega$ WITHSTAND VOLTAGE AC:150V DC:250V  
CURRENT RATING AC: 100V/0.5A DC:150V/1A
- 5.OPERATING TEMPERATURE-30°C--+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
6. OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC .

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/08/06			
TITLE				
ø3.5mm STEREO JACK ø6.3mm STEREO PLUG				
PART NO.				
63M-35F				