



REMARK:

- 1.CABLE:CAT.6 UTP 24AWG*4P(7/0.205,BARE COPPER INSULATION:PE)+CROSS JACKET: WHITE(WH02) PVC,OD:6.2±0.2mm.
- 2.CONN.:P1: 8P8C PLUG, LONG BODY, SINGLE LAY, GOLD PLATED 50u”,
P2: 8P8C JACK, PIN: GOLD PLATED, INSULATION: BLACK.
- 3.NUT: M3.0 NUT EMBEDDED.
- 4.ASS'Y BOOT:ø6.2mm (P/N: 060-BOOT-SR3-WH)
- 5.HOOD: P2: MOLDING WHITE(WH02) PVC.
- 6.CABLE ASS'Y MUST PASS CONTINUITY TEST.

WIRE CONNECTION

WIRE COLOR	P1	PAIRS	P2
WHITE/ORANGE	1	———	1
ORANGE	2	———	2
WHITE/GREEN	3	———	3
BLUE	4	———	4
WHITE/BLUE	5	———	5
GREEN	6	———	6
WHITE/BROWN	7	———	7
BROWN	8	———	8

P/N	L	T
AC6MF-PL150	150	+25/-0
AC6MF-PL1000	1000	+75/-0
AC6MF-PL3000	3000	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	09/26/13			
TITLE CAT6 JACK PANEL-MOUNT EXTENSION CABLE				
PART NO. AC6MF-PLXXXX				