



WIRE LIST

P1		P2
1	_____	1
2	_____	2
3	_____	3
4	_____	4
SHELL	_____	SHELL

REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1 AND P2:MD 4PIN FEMALE,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 3Kg TO 12Kg.
- 4.ELECTRONIC CHARCTERISTICS:CONTACT RESISTANCE:20MΩ
INSULATION RESISTANC:20MΩ WITHSTAND VOLTAGE AC:200V DC:250V
CURRENT RATING AC:100V/0.5A DC:150V/1A
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BALCK AND MATERIAL IS PVC PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE		MD4/F TO MD4/F		
PART NO.		MD4F-MD4F		