



### WIRE LIST

P1		P2
2	SHELL	2
3	CENTER	1

### REMARK:

- 1.CONSTRUCTION: SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHARTREGULATION.APPEARANCE:EVERY PART SHOULD BE FINISHED NOT TO DILAPIDTION. CRACK AND BAD FLATING.
- 2.P1:4 PIN MINI DIN FEMALE,GOLD PLATED SHELL AND P2: RCA PLUG,GOLD PLATED SHELL.
- 3.ADAPTER INSERION EXTRSCTION: FORLE 0.5Kg TO 2.0Kg.
- 4.ELECTRONIC CHARCTERISTICS: CONTACT RESISTANCE:10M  $\Omega$   
INSULATION RESISTANC: 5M  $\Omega$  WITHSTAND VOLTAGE AC:100V DC:250V,  
CURRENT RATING AC: 100V/0.3A DC:200V/1A.
5. OPERATING TEMPERATURE-30°C-+60°C AND ELECTRICAL LITE IS 5000 TIMES INSERTING LEXTRACTING CIT FALL LOAD.
- 6.OVERMOLD COLOR IS BLACK AND MATERIAL IS PVC PLASTIC.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/17/05			
TITLE RCA/M TO MD4/F ADAPTER				
PART NO. MD4F-RCAM				