



NOTE:

1. CABLE: High speed HDMI® CABLE UL20276 (28AWG*1P+AL+D+MYLAR)*4C+28AWG*1P+28AWG*5C+AL/MY+DRAIN(BARE COPPER)+BRAID(A-M ALLOY) JACKET COLOR:BLACK OD:6.5±0.15mm.
2. CONNECTOR: P1: DIN 19P MALE, SOLDER TYPE, TINNED PLATED CONTACTS, INSULATION: BLACK, NICKEL PLATED SHELL, LOCKER TYPE.
P2: DVI 24+5 FEMALE, PIN: G/F, INSULATION WHITE, NICKEL PLATED SHELL WITH METAL HEX NUT.
3. SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE DRAIN.
4. MOLDED 45P BLACK PVC.
5. TESTING: 100% ELECTRICAL TEST .
6. MOLD P/N: D14M-N01, D14M-02, DVIF-110-01, DVIF-110-N01

WIRE CONNECTION

P1	P2	COLOR	P1	P2	COLOR
1	2	WHITE	10	23	WHITE
3	1	BROWN	12	24	BLUE
2	3	DRAIN	11	22	DRAIN
4	10	WHITE	15	6	RED
6	9	RED	16	7	WHITE
5	11	DRAIN	17	15	YELLOW
7	18	WHITE	18	14	ORANGE
9	17	GREEN	19	16	PURPLE
8	19	DRAIN	SHELL	SHELL	DRAIN

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	06/15/11			
TITLE DIN19M TO DVI24+5/F				
PART NO. SICC-DVID-130				